

# **Autowave Seperator**

# FOR PROFESSIONAL USE ONLY

# Description

Powder to separate paint particles from contaminated Autowave Guncleaner.

#### **Products and additives**

Autowave Separator

#### **Basic Raw Materials**

Aluminum hydrosilicates, salts and polymers

### Application process

Autowave Guncleaner can be reclaimed by adding 1% of Autowave Separator to the contaminated Autowave Guncleaner. If necessary, add another ½-1% of Autowave Separator to coagulate the remaining contamination. All existing coagulation devices work according to the same process:

- 1. Add the Autowave Separator as specified to the contaminated Autowave Guncleaner.
- 2. Stir/mix thoroughly until paint particles have been coagulated.
- 3. Pour mixture through fine filter bag in order to separate solids from liquid, by using a fine filter bag.
- 4. The Autowave Gun Cleaner can now be used again

Autowave Gun Cleaner can effectively be recycled three times, after which, it should be disposed of.

#### **Product storage**



Product shelf-life is determined when products are stored unopened at 20°C.

Autowave Separator must be stored in closed can to avoid any contact with water/moisture dampness. After contact with water/moisture product will have limited shelf life.

Avoid extreme temperature fluctuation. Product shelf life data see TDS S9.01.02



# Use suitable respiratory protection

Akzo Nobel Car Refinishes recommends the use of a fresh air supply respirator



#### FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Coatings brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel. **Head Office** 

Akzo Nobel Car Refinishes B.V., PO Box 3 2170 BA Sassenheim, The Netherlands. www.sikkenscr.com

